## Wet End - Process Formulation (RETAN)



Nja'26 NUT WET END.x	dsx	Date: 4-Aug-20		
		Technician:	Joan Carles París	
Company:	TFL SS 25	TFL		
Type of Leather:	Shoe Upper & Leather Goods	Trial - N°:	WE 33/2023	
Aim of Trial:		Color:	tpx 17-1137	
		Piece count:	6 sides	
Project - N°:	NUT	Substance:	1,1-1,2 mm	
Material:	WW PRETANNED 6 SIDES	Weight:	18.2 KG	
% refer to:	SHAVED	Drum - N°:		

Operation	Add	%	Weight	Product	Temp.	Dilution	Time	Control
			in kg		in °C	(1 : x)	in min	
			#WERT!					
		200,00		WATER水	30			
		0,20		sodium metabisulfite亚硫酸钠				
		0,20		BORRON® SAF			45'	
DRAIN								
		150,00		WATER水	25			
		0,30		formic acid 85%甲酸			10'	pH 3,2
	+	3,00		SELLATAN <sup>®</sup> WLG LIQ			45'	
	+	3,00		CORIPOL® LEO			30'	
	+	1,50		sodium formate甲酸钠				
		2,00		SELLASOL <sup>®</sup> NG LIQ			20'	
	+	0,70		sodium bicarbonate小苏打			60'	pH 5
DRAIN								
		100,00		WATER水	25			
		5,00		LEVOTAN® HPP				
		2,00		MAGNOPAL® DP			30'	
	+	4,00		CORIPOL® WKN				
		2,00		CORIPOL® A			30'	
	+	10,00		TANIGAN® DSO LIQ				
		5,00		SELLATAN® TMC				
		1,00		CORIPOL® SLG-A			60'	
	+	10,00		TANIGAN® MBO LIQ				
		5,00		SELLATAN® TMC				
		10,00		SELLASOL® Pure H LIQ			60'	
	+	10,00		TANIGAN® MBO LIQ				
		6,00		SELLASOL® Pure RS				
		1,00		SELLASOL® TN				
		1,50		SELLA® Fast Brown HG				
		0,40		SELLA® Fast Brown H				
		0,20		BORRON® ST				
		0,15		ERGHA® GM 3034BR		run o	er night	自动过夜
	+	50.00		WATER水	35	10110	or mgm	H 77/~ IA
		3,00		formic acid 85%甲酸	- 55	2	X10'+30'	pH 3,8
		5,55		IOTHIO GOIG GO /0   FIX				F 310
					continue i	next page		
Mechanical Op	eration:			1	Process Information:			1
						Dunning Times		
					Running Time:			i

Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer from performing his own tests to determine the suitability of the supplied products for their intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere of responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application.

application..