Wet End - Process Formulation (RETAN)



Nj ă 27 STRING WET END.xlsx		Date:	3-Jul-2023	
		Technician:	Grosch	
Company:		Score:	Select Score	
Type of Leather:	Select Article	Trial - N°:	G 921	
Aim of Trial:	27 - STRING - Nubuck hidro stampato	Color:		
		Piece count:	6/2	
Project - N°:		Substance:	1,3/1,5	
Material:	WET-BLUE sh	Weight:	20,500 kg	
% refer to:	wet-blue SH	Drum - N°:		

Operation	Add	%	Weight	Product	Тетр.	Dilution	Time	Control
			in kg		in ℃	(1 : x)	in min	
		200,00	41,000	Water水	35			
		0,30	0,062	formic acid 85%甲酸		10	20	pH:3,2
Drain控水								
		100,00	20,500	Water水	35			
	+	2,00		TANIGAN [®] PAK				
		2,00	0,410	sodium formate甲酸钠			30	
	+	0,80		sodium bicarbonate小苏打			30	
	+	1,00	0,205	MAGNOPAL® DP		3	10	
	+	2,00	0,410	LEVOTAN [®] PS		3	90	pH; 5,0/5,5
Drain控水								
		200,00	41,000	Water水	30		10	
Drain控水								
		50,00	10,250	Water水	30			
		6,00	1,230	MAGNOPAL® PGN-A			30	
	+	15,00	3,075	TANIGAN® MBO LIQ		1		
		5,00	1,025	RETINGAN® Pure RS				
		2,00		BAYKANOL® TF-2N-C 01			20	
	+	1,50		SELLASOL [®] TN gran				
		4,00	0.820	BAYGENAL® Grey L-NG				
		0.50	0.103	SELLA® SET Brown M			90	Ø
	+	100,00		Waterzk	50		10	r
	+	2,00	0.410	LEUKOTAN™ 1093	30	3	20	
	- + ' +	2,00	0,410	LEUKUTAN 1093		3	20	
	+	10,00	2.050	LEVOTAN® PS		4	60	
	- + ' +	10,00	2,030	LLVOTAN F3		7	00	
	+	1,00	0.205	formic acid 85%甲酸		10	20	
	+	1,00		formic acid 65%平設		10	20	
	+	1,30		formic acid 85%甲酸		10		pH: 3,4/3,6
Drain控水		_,	0,201	Tomme deld cope page				,,,,,,
		200,00	41,000	Water水	30			
		0,50	0,103	BORRON® WP			15	
Drain控水		,	· · · · · · · · · · · · · · · · · · ·	30.4.40.4				
		150,00	30,750	Water水	30			
	+	3,00	0,615	chrome 33铬粉			90	
Drain控水								
		200,00	41,000	Water水	30		10	
Drain控水								
		200,00	41,000	Water水	30		10	
Drain控水								
,								

Mechanical Operation: Horse-up, set-out, vacuum dry 180sec@45°C, hang dry, stake

搭马,伸展,真空45℃180秒,挂晾干燥,振软

Running Time: 10 hrs 05 min

Process Information:

Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer from performing his own tests to determine the suitability of the supplied products for their intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere of responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application..