## Wet End - Process Formulation (RETAN)



Nja'4 BAJA BLUE WET END.xlsx		Date:	26-Jun-2023	
		Technician:	Tempesti	
Company:	TFL			
Type of Leather:	Shoe Upper & Leather Goods	Trial - N°:		
Aim of Trial:		Color:	18-3946	
		Piece count:		
Project - N°:	4 BAJA BLUE	Substance:	0,8-0,9	
Material:	baby calf wb	Weight:		
% refer to:	shaved weight	Drum - N°:		

Operation	Add	%	Weight in kg	Product	Temp. in °C	Dilution (1 : x)	Time in min	Control
		300,00	m ng	water水	40°C	11.00		
	+ +	1.00		formic acid 85%甲酸	40 0			
	1	0,50		CORIPOL® ICL				
		0,50		PELTEC® ADN			40	
drain	+ +	0,50		FELTEC ADIN			40	
urani	1	100,00		waterzk	40°C			
		2,00		CORIPOL® DX-1202	100			
		2,00		CORIPOL® GLH			10	
	1	5,00		TANNESCO® HN New LIQ			10	
	+ +	5,00		CHROMOSAL B			60	
		2,00		sodium formate甲酸钠			120	automatic自动过夜
drain水洗		2,00		Sociali ioiniate (Fig. ii)			120	morning pH: 3,8
didili/jt()		150,00		water水	35°C			
		2,00		TANIGAN® PAK				
		1.00		sodium formate甲酸钠			30	
		0,30		sodium bicarbonate小苏打				
		4,00		LEVOTAN® L			40	pH: 4,6-4,8
drain wash控水水洗		·						
		100,00		water:/k	30°C			
		6,00		RETINGAN® LFC			30	
		5,00		LUBRITAN <sup>™</sup> SPE			20	
		12,00		TANIGAN® MBO LIQ				
		4,00		RETINGAN® R7			20	
		2,00		TANIGAN® SR				
		х		SELLA® Fast dyestuffs			60	
		100,00		water:/k	50°C			
		Х		formic acid 85%甲酸			30	
drain wash控水水洗								
		100,00	-	waterzk	50°C			
		6,00		CORIPOL® DX-1202				
		6,00		CORIPOL® WKN				
		1,00		RODA <sup>®</sup> OIL 1449			60	
·		5,00		LEVOTAN® RP	_		30	
		0,50		formic acid 85%甲酸			30	
drain 水洗			·					

Mechanical Operation:

set out, vacuum dry 90" at 40°C

伸展, 真空40℃90秒

Process Information:

9 hrs 40 min Running Time:

Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer from performing his own tests to determine the suitability of the supplied products for their intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere of responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application.

application..